

Code: GTX-CLM1-6-4G2G

SWITCH POE **GTX-CLM1-6-4G2G** 4-PORT

Due to the reliability and ensuring high quality of transmission, the GTX-CLM1-6-4G2G 4-port PoE switch is an ideal solution for applications in CCTV IP installations. PoE powering possibility, compatible with the 802.3af/at standard makes the device more universal and easier to install.

Attention! When the Extend function is enabled the PoE range increases up to 250m and the transmission speed reduces to 10 Mb/s.



LAN ports:	<ul style="list-style-type: none"> • 4 x RJ45 (4 x PoE (802.3af/at)), • 2 x RJ45 - Uplink
Management:	✓
Transmission speed:	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 4 x Port LAN & PoE
Operation modes:	<ul style="list-style-type: none"> • EXTEND mode • Port Isolation
Default IP address:	192.168.2.1
Default admin user / password:	admin / admin
Maximal output power:	30 W / port PoE
Maximal total power:	65 W
Main features:	<ul style="list-style-type: none"> • QoS - mechanisms, which provide the high quality of transmission • Spanning Tree STP/RSTP • VLAN support - Supports up to 16 VLANs at the same time (for 4K ID VLAN addresses) • Port mirroring function • MTBF (Mean Time Between Faults) : 50000 h
LED diodes:	PWR, PoE, Link/Act
Certificates:	CE, FCC, RoHS
Protections:	Overvoltage \pm 4 kV
Power supply:	100 ... 264 V AC, Power adapter included
Housing:	Metal
Operation temp:	-10 °C ... 45 °C



DATA SHEET

Weight:	0.65 kg
Dimensions:	200 x 118 x 44 mm
Guarantee:	2 years

