

Code: H2A

IP PTZ CAMERA INDOOR **H2A** Hero A1 Wi-Fi - 1080p 3.6 mm DAHUA

IP PTZ camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at max. resolution of 1080p.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m. The camera has no built-in web interface, configuration only through the DMSS application.

The device is ideal for eg. as a baby monitor, with mobile image view on smartphone and possibility of bi-directional audio transmission.



Standard:	IP
Resolution:	1920 x 1080 - 1080p
Sensor:	1/3.2 " Progressive Scan CMOS
Lens:	3.6 mm
View angle:	79 °
Range of IR illumination:	10 m
Horizontal rotation range:	355 °
Vertical rotation range:	-5 ° ... 80 °
Audio:	<ul style="list-style-type: none"> • Microphone built-in, • Speakers built-in, • Bi-directional audio streaming support
Image compression method:	H.265
Main stream frame rate:	25 fps @ 1080p
Interface:	<ul style="list-style-type: none"> • 10/100 Base-T (RJ-45), • Wi-Fi IEEE 802.11 b/g/n



DATA SHEET

WEB Server:	—
ONVIF:	—
Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application DMSS• iOS (iPhone): Free application DMSS
Default IP address:	DHCP
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	—
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	—
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Main features:	<ul style="list-style-type: none">• Wi-Fi Module - IEEE 802.11 b/g/n - 2.4 GHz• D-WDR - Wide Dynamic Range• Image rotation and mirror• Motion Detection - max. 4 zones• Intelligent recognition of the human figure and tracking the movement of a person
Power supply:	5 V DC / 1 A (power adapter included)
Power consumption:	≤ 5 W
Housing:	Plastic
Color:	White
"Index of Protection":	—
Mechanical protection class:	—
Operation temp:	0 °C ... 60 °C
Weight:	0.2 kg
Dimensions:	Ø 78 x 108 mm
Supported languages:	English, Polish
Manufacturer / Brand:	DAHUA
Guarantee:	3 years