

Code: SDR-120-24

SWITCHING ADAPTER **SDR-120-24** MEAN WELL

Switching adapter installed on the TS35/7.5 or 15 DIN rail, resistant to high operation temperatures (up to 70°C).

The power supply has been equipped with a relay that indicates the status of the DC output.



| | |
|------------------------------|---|
| Adapter type: | Switching |
| Power voltage: | <ul style="list-style-type: none"> • 88 ... 264 V AC • 124 ... 370 V DC |
| Output voltage: | 24 V DC |
| Output voltage adjustment: | 24 ... 28 V DC |
| Maximal load: | 5 A |
| Output power: | 120 W |
| Instantaneous maximum power: | 180 W - 3 s (max) |
| Number of outputs: | 1 pcs |
| Efficiency: | 88 % |
| Housing type: | DIN |
| Relay output: | 1 pcs - DC OK |



DATA SHEET

| | |
|--------------------------------------|---|
| Protections: | <ul style="list-style-type: none">• Short-circuit• Overload• Overvoltage• Overheat |
| Operation temp. / Relative humidity: | -25 °C ... 70 °C / 20 ... 95 % |
| Weight: | 0.62 kg |
| Dimensions: | 125 x 124 x 41 mm |
| Manufacturer / Brand: | MEAN WELL |
| Guarantee: | 3 years |