

Code: TM-LI-OFFICEPRO-600-F2

UPS **TM-LI-OFFICEPRO-600-F2** 600 VA IPS

The TM-LI-OFFICEPRO-600-F2 UPS is intended for office equipment, telecommunications systems and CCTV security systems. The UPS ensures stable operation of the devices connected to it in the event of a power outage.

The TM-LI-OFFICEPRO-600-F2 model has a built-in AGM battery.



| | |
|--|---|
| Power adapter type: | Line-interactive |
| Nominal power: | 360 W |
| Apparent Power: | 600 VA |
| Input voltage: | 162 V ... 295 V AC |
| Input frequency: | 50 / 60 Hz (auto detection) |
| Output voltage: | 230 V AC \pm 5 % (Approximated Sine Wave) |
| Output frequency: | 50 / 60 Hz \pm 1 % |
| Power factor: | 0.6 |
| Voltage adjustment: | — |
| Frequency adjustment: | — |
| Transfer time: | 2 ... 7 ms (typical) max. 10 ms |
| Charging time (recover to 90% capacity): | 5 ... 8 hours |
| Battery: | 1 pcs - 12V/7Ah AGM |



DATA SHEET

| | |
|--------------------------------------|---|
| Estimated battery operation time: | <ul style="list-style-type: none">• 2 minutes @ 100 %,• 5 minutes @ 75 %,• 8 minutes @ 50 %,• 10 minutes @ 25 % |
| Number of outputs: | 2 pcs CEE 7/3 (Schuko) |
| Management software: | UPSmart (Windows 98/2000/2003/XP/Vista/2008/7/8/10) |
| Protections: | <ul style="list-style-type: none">• Fuse• Overload• Short-circuit• Overvoltage• Temperature• Overcharge• Protection against deep discharge of the battery• Telephone line filter |
| Operation state indication: | <ul style="list-style-type: none">• LCD display: operation mode, battery charging level, in/out voltage level, Work load,• Sound signaling |
| Main features: | <ul style="list-style-type: none">• Microprocessor control system• UPS auto diagnostic system• Auto restart while AC is recovering• COLD START: - Cold start of the power adapter• Automatic battery charging in OFF mode• Built-in AVR voltage stabilization system• Built-in EMI, RFI filter• 2 x RJ-11 - Input / Output• Communication interface - Port USB• USB A / USB B cable included |
| Application: | <ul style="list-style-type: none">• to Home & Small Office applications• Telecommuniacion• CCTV - Surveillance Systems |
| Housing type: | Tower |
| Operation temp. / Relative humidity: | 0 °C ... 40 °C / 20 ... 90 % |
| Weight: | 4.37 kg |
| Dimensions: | 305 x 90 x 165 mm |
| Manufacturer / Brand: | IPS |
| Guarantee: | 2 years |