

Code: SO-MF3-W

PROXIMITY READER **SO-MF3-W** SATEL

Proximity card reader.



Cards support:	13.56 MHz S50 : Ultralight CSN/SSN, Classic CSN/SSN/MSN, DESFire (EV1 / EV2 / EV3) CSN/MSN
Reading distance of prox-keys:	max. 5 cm
Relay output:	1 pcs
Relay contacts rating (resistive load):	1 A / 30 V
Keyboard built-in:	—
Autonomous operation:	✓
Operation modes:	<ul style="list-style-type: none"> • Proximity card reader for INTEGRA alarm system, • Proximity card reader for ACCO NET or ACCO access control system, • Wiegand Reader, • standalone door control module
Tamper output:	✓
Communication:	<ul style="list-style-type: none"> • Wiegand 26-66bit • Open Supervised Device Protocol (OSDP) • EM-MARIN

Main features:	<ul style="list-style-type: none">• Tamper protection (detection of removing from mounting surface and enclosure opening)• LED indication• Beep signal
Color:	White
Power supply:	12 V DC
Average current consumption:	63 mA
Operation temp:	-25 °C ... 55 °C
Permissible relative humidity:	max. 93 %
Weight:	0.09 kg
Dimensions:	128 x 45 x 21 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years