

Code: SDT4E425-4F-GB-A-PV1-0400

IP SPEED DOME CAMERA **SDT4E425-4F-GB-A-PV1-0400** PANORAMIC TiOC WizSense Smart Dual Light - 3.7 Mpx 5 ... 125 mm, 2.8 mm DAHUA

The Speed Dome IP camera, in addition to the traditional PTZ camera module, also has a panoramic camera module mounted in the same housing. The series of these cameras can be used to monitor large spaces in high definition, such as rivers, roads, railways, airports, squares, parks, meeting places, etc. Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image.

The **DAHUA TiOC** series of cameras are modern IP cameras combining 3 innovative technologies: **Dahua Full-Color** - 24/7 color image, **Wiz-Sense** - AI artificial intelligence functions and audio-visual **active deterrence** (flashing red and blue lights and a siren sound).

The panoramic camera connects to the PTZ camera to track targets. Once a target enters the panoramic area, the PTZ camera begins monitoring the target and tracks its movement by panning, zooming and focusing the lens, allowing the camera to generate highly detailed images of the targets' movements for security personnel. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3at standard makes the device more universal and easier to install.



Standard:	IP
Resolution:	Camera PTZ, Panoramic camera : <ul style="list-style-type: none"> • 2560 x 1440 - 3.7 Mpx, • 2048 x 1536 - 3 Mpx, • 2304 x 1296 - 3 Mpx, • 1920 x 1080 - 1080p, • 1280 x 960 - 1.3 Mpx, • 1280 x 720 - 720p
Sensor:	<ul style="list-style-type: none"> • Camera PTZ : 1/2.8 " STARVIS™ CMOS, • Panoramic camera : 1/2.8 " Progressive Scan CMOS
Lens:	<ul style="list-style-type: none"> • Camera PTZ : 5 ... 125 mm • Panoramic camera, : 2.8 mm
View angle:	<ul style="list-style-type: none"> • Camera PTZ : 52 ° ... 3 °, • Panoramic camera : 101 °
Optical zoom:	x 25
Digital zoom:	x 16



DATA SHEET

Range of IR illumination:	<ul style="list-style-type: none">• 100 m @ Camera PTZ• 30 m @ Panoramic camera
White light LED illuminator range:	<ul style="list-style-type: none">• 50 @ Camera PTZ• 30 @ Panoramic camera
Preset rotation speed:	<ul style="list-style-type: none">• 240 °/s (horizontal)• 200 °/s (vertical)
Rotation speed (manual control):	<ul style="list-style-type: none">• 0.1 °/s ... 200 °/s (horizontal)• 0.1 °/s ... 120 °/s (vertical)
Horizontal rotation range:	360 ° - continuous
Vertical rotation range:	-15 ° ... 90 °
RS-485 interface:	—
Number of presets:	300
Horizontal scan:	✓
Route settings:	8
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	2 / 1
Audio:	<ul style="list-style-type: none">• External microphone input• Audio output• Audio detection• Speaker built-in - Alarm siren• Bi-directional audio streaming support• Digital Noise Reduction
Main stream frame rate:	<ul style="list-style-type: none">• Camera PTZ : 25 fps @ 4 Mpx• Panoramic camera : 25 fps @ 4 Mpx
Network interface:	10/100 Base-T (RJ-45)
Memory card slot:	Micro SD card support up to 512GB
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	✓
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream





DATA SHEET

Intelligent Image Analysis:	<ul style="list-style-type: none">• Intelligent Object Tracking• crossing the line (tripwire)• detection of entry into the area / exit from the area• intrusion• fast moving• classification of people and vehicles• crowd gathering estimation
Main features:	<ul style="list-style-type: none">• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality• Active deterrence function - Light and sound alarm - Active intrusion deterrence works by blinking blue and red light and siren sound or voice prompts• WDR - 120 dB - Wide Dynamic Range• 2D-DNR, 3D-DNR - Digital Noise Reduction• F-DNR (Defog) - Reduction of image noise caused by precipitation• EIS - Electronic Image Stabilization• ROI - improve the quality of selected parts of image• Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles• SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms• Image rotation and mirror• BLC/HLC - Back Light / High Light Compensation• ICR - Movable InfraRed filter• Day/night mode• Auto White Balance• Sharpness - sharper image outlines• Configurable: brightness, contrast, saturation• NAS - Network Attached Storage support• Configurable Privacy Zones• Motion Detection• Filtering of false alarms based on the recognition of persons and vehicles
Housing:	Speed Dome, Plastic
Color:	White + Black
"Index of Protection":	IP66
IK rating:	—
Power supply:	<ul style="list-style-type: none">• PoE (802.3at),• 12 V DC / 3 A
Power consumption:	<ul style="list-style-type: none">• ≤ 12 W (typical),• 25 W (max)
Operation temp:	-40 °C ... 65 °C
Weight:	3.4 kg
Dimensions:	152 x 185 x 305 mm (without bracket)
Supported languages:	Polish, English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years