

Code: RG-ES228GS-P

## SWITCH POE **RG-ES228GS-P** 24-PORT SFP REYEE

Due to the reliability and ensuring high quality of transmission, the RG-ES228GS-P 24-port PoE switch is an ideal solution for applications in CCTV IP installations. 24 ports support Power over Ethernet (PoE) function.

Switch is managed through the web and the cloud (Ruijie Reyee application).



LAN ports:	<ul style="list-style-type: none"> <li>• 26 x RJ45 10/100/1000 Base-T ( 24 x PoE (802.3af/at) ),</li> <li>• 2 x port SFP 1000 Base-X - Uplink</li> </ul>
Management:	✓
Number of fan coolers:	1 pcs
LED diodes:	SYSTEM indicator, PoE, Link/Act, SFP
Transmission speed:	<ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps : 24 LAN &amp; PoE ports + 2 LAN ports,</li> <li>• 1000 Mbps : 2 SFP ports</li> </ul>
Maximal total power:	370 W
Switching capacity:	56 Gb/s
Forwarding rate:	41.664 Mpps
MAC addresses table:	8k
Mobile phones support:	Android: <a href="#">Ruijie Reyee</a> free application iOS (iPhone): <a href="#">Ruijie Reyee</a> free application
Default IP address:	10.44.77.200
Main features:	<ul style="list-style-type: none"> <li>• Switch is managed through the web and the cloud (Ruijie Reyee application)</li> <li>• Can be mounted in a Rack cabinet,</li> <li>• Supports up to 16 VLANs at the same time (for 4K ID VLAN addresses)</li> <li>• DHCP client</li> <li>• DHCP snooping support</li> <li>• Port mirroring function</li> <li>• Loop Protection</li> <li>• IEEE802.3x Flow Control</li> <li>• MTBF (Mean Time Between Faults) &gt; 200.000 h</li> </ul>
Certificates:	CE, RoHS
Protections:	Protection against lightning discharges : 4 kV
Housing:	Rack 19", Metal
Power supply:	100 ... 240 V AC
Power consumption:	≤ 391 W



# DATA SHEET

Operation temp:	0 °C ... 40 °C
Weight:	2.8 kg
Dimensions:	440 x 215 x 44 mm / RACK 19", 1U
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	<b>3 years</b>