

Code: RG-EW3000GXPRO

## ROUTER **RG-EW3000GXPRO** Wi-Fi 6, 2.4 GHz, 5 GHz 574 Mbps + 2402 Mbps REYEE

With 1201 Mbps wireless speeds over the crystal clear 5 GHz band and 574 Mbps over the 2.4 GHz band, RG-EW3000GXPRO offers you the flexibility of 2 dedicated networks and ensures amazing wireless performance. Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band - all at the same time.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes. 4 external antennas provide stable omnidirectional signal and superior wireless coverage.



Frequency range:	2.4 GHz, 5 GHz
Antenna type:	5 x Omnidirectional antenna - Integrated : • 5 dBi @ 5 GHz 2x2 MU-MIMO • 5 dBi @ 2.4 GHz 2x2 MU-MIMO
Standards:	IEEE 802.11 b/g/n/ac/ax @ 2.4 GHz , IEEE 802.11 a/n/ac/ax @ 5 GHz
Baud rates:	574 Mbps + 2402 Mbps
LAN ports:	3 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink
LED indicators:	Status, Mesh
DDNS:	✓
DHCP server:	✓
Firmware update:	✓
Protections:	WPA2/WPA3 DoS attack defense



# DATA SHEET

Management interface:	Web browser, Configuration using the Reyee Router application
Mobile phones support:	Android: Free application <a href="#">Reyee Router</a> iOS (iPhone): Free application <a href="#">Reyee Router</a>
Transmitter power:	max. 20 dBm @ 2.4 GHz max. 27 dBm @ 5 GHz
Power supply:	12 V DC / 1.5 A (power adapter included)
Power consumption:	≤ 18 W
Main features:	<ul style="list-style-type: none"><li>• Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments</li><li>• Support for Reyee Mesh technology,</li><li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li><li>• Static / dynamic routing</li><li>• Built-in 3-port switch</li><li>• Access Point</li><li>• WMM support (QoS mechanism of the 802.11e standard)</li><li>• Remote management</li><li>• DMZ</li><li>• UPnP</li><li>• IPTV compliance</li><li>• Port forwarding</li><li>• parental control</li><li>• Guest Network - a separate and secure network for guests</li><li>• DHCP client list</li><li>• SSID hiding</li><li>• System logs</li><li>• IPv6 compliance</li><li>• PPTP VPN Server / Client</li><li>• WAN aggregation</li><li>• RESET button</li><li>• MESH button</li></ul>
Operation temp:	-10 °C ... 45 °C
Permissible relative humidity:	5 % ... 95 % (non-condensing)
Weight:	0.49 kg
Dimensions:	260 x 140 x 30 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	2 years