

Code: GTX-B1-18-16G1SFP/X

SWITCH POE **GTX-B1-18-16G1SFP/X** 16-PORT SFP

Due to the reliability and ensuring high quality of transmission, the GTX-B1-18-16G1SFP/X 16-port PoE switch is an ideal solution for applications in CCTV IP installations. PoE powering possibility, compatible with the 802.3af/at standard makes the device more universal and easier to install.

Attention! When the Extend function is enabled the PoE range increases up to 300m and the transmission speed reduces to 10 Mb/s.



LAN ports:	<ul style="list-style-type: none"> • 16 x RJ45 (16 x PoE (802.3af/at)), • 2 x RJ45 - Uplink, • 1 x Port SFP Uplink
Management:	—
LED diodes:	Power, Link/Act
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 Mbps - 16 x Port LAN & PoE, • 1000 Mbps - 2 x Port RJ-45 + 1 x Port SFP - Uplink
Operation modes:	<ul style="list-style-type: none"> • AI Watchdog mode • EXTEND mode - Range PoE 300 m • Port isolation - VLAN mode
Maximal output power:	30 W / port PoE 802.3af/at - 1 ... 16 ports
Maximal total power:	200 W
MAC addresses table:	8k
Main features:	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Auto-learning and Auto-aging functions support for MAC addresses • Support for power priority mechanism • Can be mounted in a Rack 19" cabinet
Certificates:	CE
Protections:	Overvoltage \pm 4 kV
Power supply:	230 V AC
Housing:	Desktop, Metal
Operation temp:	-20 °C ... 55 °C
Weight:	1.6 kg
Dimensions:	310 x 205 x 44 mm
Manufacturer / Brand:	GTX - Grid Telecommunication eXpert



DATA SHEET

Guarantee:	2 years
------------	---------