

Code: DS-7604NXI-K1(D)

NVR **DS-7604NXI-K1(D)** 4 CHANNELS AcuSense Hikvision

NVR equipped with advanced functions of intelligent image analysis.



| | |
|-------------------------------|---|
| Supported standards: | IP |
| Number of supported channels: | 4 |
| Supported resolutions: | 12 Mpx |
| AI powered by recorder: | <ul style="list-style-type: none"> • Face recognition - Comparison of faces with images from the database, Support for up to 16 face databases, including 20 000 face images, Smart search for a person based on a face photo • Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians • Smart motion detection (with recognizing people and vehicles) - Filtering of false alarms based on the recognition of persons and vehicles |
| AI powered by cameras: | <ul style="list-style-type: none"> • Face recognition • Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians • Intelligent Object Tracking • Smart motion detection (with recognizing people and vehicles) • ANPR • VCA - metadata support |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Hik-Connect free application • iOS: Hik-Connect free application |
| Supported hard drives: | 1 x 16 TB SATA |
| Video outputs: | 1 pcs HDMI 4K 1 pcs VGA |
| Bitrate: | 40 Mbps (incoming) |
| Audio inputs: | 1 pcs CINCH |



DATA SHEET

| | |
|----------------------------------|---|
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Network interface: | 1 x RJ-45 10/100/1000 Base-TX |
| ONVIF: | ✓ |
| Default IP address: | 192.168.1.64 |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Web browser access ports: | 80, 8000 |
| PC client access ports: | 8000 |
| USB: | 2 pcs USB 2.0 |
| Alarm inputs / outputs: | — |
| Switch PoE: | — |
| Power supply: | 12 V DC / 1.5 A (power adapter included) |
| Power consumption: | max. 10 W (without HDD) |
| Operation temp: | -10 °C ... 55 °C |
| Weight: | 1.11 kg |
| Dimensions: | 320 x 245 x 48 mm |
| Supported languages: | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 303621188 |
| Guarantee: | 3 years |