

Code: DS-K1T320MWX

ACCESS CONTROLLER WITH FACE RECOGNITION **DS-K1T320MWX** - 720p Hikvision



Access controller with face recognition function. The device also has functions that allow to register working time.

Sensor:	CMOS
Matrix size:	2 Mpx
Resolution:	1280 x 720 - 720p

Access control:

Cards support:	13.56 MHz S50 / M1
Memory:	<ul style="list-style-type: none"> • Memory of 500 face templates • Memory of 1000 RFID cards • Non-volatile log buffer of the last 100 000 events

General information:

Standard:	IP
IR illuminator:	—
LED illuminator:	—
Video output:	—
RS-485 interface:	✓



DATA SHEET

Memory card slot:	—
Alarm inputs / outputs:	—
Audio:	Speaker built-in
Network interface:	<ul style="list-style-type: none">• 10/100/1000 Mbps (RJ-45)• Wi-Fi : IEEE 802.11 b/g/n
Network protocols:	TCP/IP, ISUP, ISAPI
WEB Server:	Built-in
ONVIF:	—
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	port 8000
Main features:	<ul style="list-style-type: none">• LCD display : 2.4 "• Keyboard built-in• Mechanical tamper protection• Open the door using face recognition, card, PIN code or any combination of the above• AI detection : Face recognition• Face anti-spoofing - intelligent security system that prevents the door from being opened with a photo or mask• Configuration and management from the iVMS-4200 application• Port USB• Door lock control output• Possibility to connect an exit button and a reed switch to control the door status
Power supply:	12 V DC / 0.5 A
Power consumption:	≤ 6 W
Housing:	Metal
Color:	Black / Silver
"Index of Protection":	—
Operation temp:	-30 °C ... 60 °C
Weight:	0.19 kg
Dimensions:	150 x 130 x 25 mm (without bracket)
Supported languages:	English, Polish
Manufacturer / Brand:	Hikvision
SAP Code:	302919142
Guarantee:	3 years