

Code: APTI-POE0402-60W-ECO

## SWITCH POE **APTI-POE0402-60W-ECO** 4-PORT

Due to the reliability and ensuring high quality of transmission, the APTI-POE0402-60W-ECO 4-port PoE switch is an ideal solution for applications in CCTV IP installations.

**Attention!** When the Extend function is enabled the PoE range increases up to 250m and the transmission speed reduces to 10 Mb/s.



LAN ports:	<ul style="list-style-type: none"> <li>• 4 x RJ45 10/100 Base-TX ( 4 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 10/100 Base-TX - Uplink</li> </ul>
Transmission speed:	<ul style="list-style-type: none"> <li>• 10 / 100 Mbps : 4 x Port LAN &amp; PoE,</li> <li>• 10 / 100 Mbps : 2 x Port RJ45 (Uplink)</li> </ul>
Maximal output power:	30 W / port PoE - 1 ... 4 ports
Maximal total power:	60 W
MAC addresses table:	1k
Management:	—
Operation modes:	E+V - Extend On : 250 m @ 10 Mbps - 1 ... 4 ports
LED diodes:	Power, Extend, Link/Act, PoE
Main features:	<ul style="list-style-type: none"> <li>• Power supply PoE, Endspan mode support : 1-2(+), 3-6(-)</li> <li>• EXTEND mode - 1 ... 4 ports</li> <li>• Port PoE Priority</li> <li>• Auto-learning and Auto-aging functions support for MAC addresses</li> <li>• Full Duplex: IEEE802.3x, Half Duplex: Back Pressure</li> <li>• Data Flow Control (802.3x)</li> <li>• Mounts for mounting the device in the RACK 10" system</li> </ul>
Certificates:	CE
Housing:	Metal
Power supply:	110 ... 240 V AC, 50 / 60 Hz
Power consumption:	max. 78 W
Operation temp:	-10 °C ... 55 °C
Weight:	0.6 kg



# DATA SHEET

---

Dimensions:	200 x 122 x 45 mm
Manufacturer / Brand:	APTI
Guarantee:	2 years