

Code: TEDEE-DRY-CONTACT

## LOCK WIRED MODULE **TEDEE-DRY-CONTACT** Tedee GERDA

This accessory allows to connect Tedee PRO, Tedee GO locks with classic wired control systems. The TEDEE-DRY-CONTACT module allows you to control your locks with smart home systems, control panels and push buttons, without the need for apps or the cloud.

The module allows you to open and close the Tedee lock via Dry Contact logic inputs. The lock is controlled via Bluetooth. The module has two outputs: signaling the "open" status and low battery level of the lock.

**Attention!** Installation should be done within Bluetooth signal range from the lock. The module requires a one-time activation in the Tedee application.



Application:	TEDEE-GO, TEDEE-PRO, TEDEE-BRIDGE
Inputs:	2 x NO
Outputs:	2 x NO
Wireless:	Bluetooth, 2.4 GHz - BLE 5.2

Main features:	<ul style="list-style-type: none"><li>• Integration with any system</li><li>• No Internet connection required</li><li>• Simple configuration</li><li>• Options tailored to the scenarios in app</li><li>• Direct connection of locks to alarm systems</li><li>• Use in critical infrastructure installations</li><li>• Local integration with compatible smart home systems</li><li>• Use with automatic door openers</li><li>• Operation via simple manual controls like buttons and switches</li><li>• RESET button</li></ul>
Housing:	Plastic (PC + ABS)
Color:	Black
Power supply:	5 ... 60 V DC (screw terminals)
Operation temp:	0 °C ... 60 °C
Permissible relative humidity:	0 % ... 90 %
Weight:	0.022 kg
Dimensions:	57 x 44 x 16 mm
Manufacturer / Brand:	GERDA / Tedee
Guarantee:	2 years