

Code: DS-3E1510P-EI/M

SWITCH POE **DS-3E1510P-EI/M** 8-PORT Hikvision

The DS-3E1510P-EI/M PoE Switch is an industrial type device enabling fluent network transmission at rates 1000 Mbps.



LAN ports:	<ul style="list-style-type: none"> • 8 x RJ45 (8 x PoE (802.3af/at)), • 2 x RJ45 (Uplink)
Management:	✓
LED diodes:	Power, Link/Act, PoE, PoE Max, 9 Uplink, 10 Uplink
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 8 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 RJ45 (Uplink) ports
Maximal output power:	30 W / port PoE
Maximal total power:	60 W
Switching capacity:	20 Gb/s
Forwarding rate:	14.88 Mpps
MAC addresses table:	4k
Default IP address:	10.180.190.200
Default admin user / password:	admin / -
Operation modes:	<ul style="list-style-type: none"> • Long Range - 300 m, 10 Mbps - 1 ... 8 ports • Port Isolation - 1 ... 8 ports • Watchdog PoE - 1 ... 8 ports

Main features:	<ul style="list-style-type: none"> • Switch is web managed • Configuration and management from the iVMS-4200 application • Hik-Central Pro support • HPP - Hik-Partner Pro support - View topology and network status, Data Flow Control , Remote update of software, Remote configuration • Port Isolation - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • PoE Watchdog mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • Static link aggregation - Link aggregation is used to aggregate multiple physical ports to form a logical port for load balancing, bandwidth expansion, and port protection • Support 3 aggregation groups • Loop Protection - IEEE 802.1d, IEEE 802.1w, Spanning Tree STP/RSTP • VLAN - IEEE 802.1Q standard support, up to 32 VLAN groups and 1 ... 4094 VIDs • Cable test • Compliance with the LLDP protocol • SNMPv1/v2c • Port mirroring function • Power supply PoE : Endspan mode support 1-2(-), 3-6(+) • RESET button • Possibility to mount to the wall
Certificates:	CE, RoHS, WEEE
Protections:	Overvoltage 6 kV - PoE ports
Housing:	Metal
Color:	Graphite
Power supply:	54 V DC / 1.2 A (power adapter included)
Power consumption:	max. 65 W
Operation temp:	0 °C ... 40 °C
Weight:	0.5 kg
Dimensions:	218 x 109 x 28 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301802997
Guarantee:	3 years