

Code: DS-3E1518P-EI(V2)

SWITCH POE **DS-3E1518P-EI(V2)** 16-PORT SFP Hikvision

The DS-3E1518P-EI(V2) switch is designed for large streams of video data in the CCTV IP surveillance networks.

Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	<ul style="list-style-type: none"> • 16 x RJ45 10/100/1000 Base-T (16 x PoE (802.3af/at)), • 1 x SFP 1000 Base-X - Uplink, • 1 x RJ45 10/100/1000 Base-T - Uplink
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 16 LAN & PoE ports, • 10 / 100 / 1000 Mbps - Port Uplink, • 1000 Mbps - Port SFP
Maximal output power:	30 W / port PoE
Maximal total power:	230 W
MAC addresses table:	8 k
Management:	✓
Default IP address:	10.180.190.200
Default admin user / password:	admin / -
Operation modes:	<ul style="list-style-type: none"> • Extend On : 300 m, 10 Mbps @ UTP cat. 5e, 6 • Extend Off : 100 m, 1000 Mbps @ UTP cat. 5e, 6
Main features:	<ul style="list-style-type: none"> • Link aggregation is used to aggregate multiple physical ports to form a logical port for load balancing, bandwidth expansion, and port protection • Support static link aggregation • Support 8 aggregation groups • Configuration and management from the iVMS-4200 application • View topology and network status • Data Flow Control • Statistical Reporting • Remote configuration • Remote update of software • 6 kV protection against lightning discharges and voltage differences and strokes between devices
LED diodes:	Power, Link/Act, PoE, PoE Max, 17 Port Uplink, 18 Port Uplink
Certificates:	CE



DATA SHEET

Power supply:	100 ... 240 V AC
Operation temp:	0 °C ... 45 °C
Weight:	2.57 kg
Dimensions:	440 x 221 x 44 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301802747
Guarantee:	3 years