

Code: PFS3016-16GT-M

Switch **PFS3016-16GT-M** 16-PORT DAHUA

The PFS3016-16GT-M switch is designed for large streams of video data in the CCTV IP surveillance networks. Designed to continuous operation 24/7.



LAN ports:	<ul style="list-style-type: none"> • 14 x RJ45, • 2 x RJ45 (Uplink)
Management:	—
LED diodes:	Power, Link/Act
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 14 LAN ports, • 10 / 100 / 1000 Mbps - 2 Uplink ports
Switching capacity:	32 Gb/s
Forwarding rate:	23.68 Mpps
MAC addresses table:	8k
Operation modes:	V - VLAN (Port Isolation) - 1 ... 14 ports are isolated from each other and separately work with the 15, 16 ports
Main features:	<ul style="list-style-type: none"> • Port isolation • Plug & Play • Possibility to mount to the wall
Certificates:	CE
Protections:	<ul style="list-style-type: none"> • Protection against lightning discharges : 2 / 1 kV (common/differential) • Protection against electrostatic discharge : 6 / 8 kV Contact/Air (ESD/EMP)
Housing:	Desktop, Metal
Color:	Graphite
Power supply:	12 V DC / 1 A (power adapter included)



DATA SHEET

Power consumption:	max. 12 W
Operation temp:	-10 °C ... 55 °C
Weight:	0.58 kg
Dimensions:	235 x 103 x 27 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years