DATA SHEET

Code: LZ-6/POL

POWER SUPPLY DISTRIBUTOR **LZ-6/POL**

The LZ-6/POL is a passive device and allows to distribute the power supply.
The housing of the LZ-6/POL has been prepared for mounting with screws to a wall or with a tie to a mast (tie, screws - not included).
An unquestionable advantage of employing the LZ-6/POL in monitoring systems powered from a central point is additional tamper protection. Without individual protection for each power line, an intruder can stop powering of the whole system just by shorting out the power line of the single camera.



Number of power inputs:	2
Number of power outputs:	6
Maximal power voltage:	24 V DC (typical 12V)
Maximal power supply current:	• 9 A terminals • 4 A 5.5/2.1 socket
Max. output current for single output:	1.5 A
Protection type:	6 x 1.5 A Polymer fuse
Power connectors type:	Input : socket 2.1/5.5 mm / Cable terminals Output : Cable terminals
Operation temp:	-50 °C ... 55 °C
Permissible relative humidity:	< 95 %
Dimensions:	120 x 91 x 37 mm
Weight:	0.099 kg
Manufacturer / Brand:	DELTA
Guarantee:	**3 years**

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60