

Code: AXON-MULTINET-24

OVERVOLTAGE LIMITER **AXON-MULTINET-24** ETHERNET RACK

The AXON-MULTINET-24 is multi-channel overvoltage protection device designed to overvoltage protection of devices connected to the Ethernet 10/100/1000 Mb/s networks, such as: network cards, hubs, switches, routers, etc. It has 24 independent channels (in/out), for each channel the device protects all 4 wires of the UTP cable carrying away the discharge current to the ground.

The AXON-MULTINET-24 is designed to mount inside RACK 19" cabinet as 1U module.



Sockets type:	24 x RJ-45 (8-pin, 4 pairs)
Protected pairs of wires:	1-2, 3-6, 4-5, 7-8
Rated voltage:	20 V
Maximal voltage:	25 V
Voltage protection level (line-line):	40 V
Voltage protection level line-PG:	600 V
Nominal discharge current (line-line):	100 A (8/20 μ s)
Nominal discharge current (line-PG):	100 A (8/20 μ s)
Maximal discharge current (line-line):	135 A (8/20 μ s)
Maximal discharge current (line-PG):	135 A (8/20 μ s)
Capacity:	20 pF
Dimensions:	490 x 85 x 44 mm
Weight:	1.5 kg
Guarantee:	2 years