

Code: VMT-425M

## MONITOR VGA, 2XVIDEO IN, 2XVIDEO OUT, S-VIDEO, HDMI, AUDIO, REMOTE CONTROLLER **VMT-425M** 42 " VILUX

CCTV monitor with solid metal housing. The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination.

It has two types of mounting. As standalone with included stands and VESA 200 and VESA 400x200 mounting. This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems.

Monitor is designed to the display of advertising spots from computer in public places such as waiting rooms, etc. Very interesting solution is placing the speakers of the back side of housing. It does not bother listening to the AUDIO from the recorder at the same time does not reduce the area of the monitor front panel.

The device is designed to continuous work in closed spaces.



Screen size:	42 "
Native resolution:	1920 x 1080 px
Aspect ratios:	16 : 9
Matrix type:	TFT-LCD color matrix
Matrix backlight:	In LED technology
Supported standards:	PAL/NTSC
Contrast:	1200 : 1
Brightness:	500 cd/m <sup>2</sup>
Viewable angles:	160 ° horizontal 140 ° vertical
Response time:	6 ms
Speakers built-in:	2 x 10 W
Signal connectors:	<ul style="list-style-type: none"> <li>• Composite Video (BNC) sockets: 2x in, 2x out</li> <li>• 1x VGA</li> <li>• 1x HDMI</li> <li>• 1x S-VIDEO</li> <li>• Audio input: (Jack - works with VGA input)</li> <li>• 2x audio input: 2x Cinch L/R - works with BNC input</li> </ul>
Housing type:	Metal
Monitor mounting standard:	VESA 200 VESA 400x200



# DATA SHEET

Power supply:	230 V AC
Power consumption:	max. 110 W (operation)
Monitor control:	OSD - by IR remote controller or monitor control keys
Main features:	<ul style="list-style-type: none"><li>• 3D Comb Filter</li><li>• 3D Noise Reduction</li><li>• PIP and POP functions - picture in picture and two pictures side by side</li><li>• Auto Picture Adjustment</li></ul>
Operation temp:	-20 °C ... 60 °C
Weight:	18 kg
Dimensions:	984 x 644 x 199 mm
Supported languages:	English, Chinese, French, Spanish, German, Portuguese, Russian, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years