

Code: VI-1000/LCD

UPS **VI-1000/LCD** 1000 VA

The VI-1000/LCD UPS is a professional device used to maintain the operation of the components connected to it. Additionally protects the connected equipment against overvoltages.



Nominal power:	600 W
Apparent Power:	1000 VA
Input voltage:	162 ... 290 V AC
Output voltage:	230 V AC (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Charging time (recover to 90% capacity):	4 ... 6 hours
Estimated battery operation time:	11 minutes @ 240 W
Battery:	2 x 12V/7Ah
Number of outputs:	2 pcs
Number of inputs:	2 pcs
Transfer time:	2 ... 6 ms (max. 10 ms)
Management software:	ViewPower (Polish version - Windows 98/2000/XP/Vista/7/8, MAC, Linux, FreeBSD, Solaris)
Additional protection:	RJ11, RJ45
Protections:	<ul style="list-style-type: none"> • Overcharge • Discharge • Short-circuit



DATA SHEET

Main features:	<ul style="list-style-type: none">• Auto restart while AC is recovering• Short-time charging• Excellent microprocessor control guarantees high reliability• Built-in AVR voltage stabilization system• Battery charging at power-off mode• "Cold Start" function• USB interface• Energy Saving function (possibility to deactivate from software)
Application:	to Home & Small Office applications
Operation state indication:	LCD display: operation mode, battery charging level, in/out voltage level
Housing type:	Tower
Dimensions:	344 x 147 x 163 mm
Weight:	8.4 kg
Guarantee:	2 years