DATA SHEET

Code: GMDF-352

MULTIMEDIA OUTLET **GMDF-352**

The multimedia subscriber outlet is designed to indoor use for group CATV installations, where return path is used for data transmission services like Internet or VoIP telephony.

The outlet divides the sum of transmitted signals in coaxial cable into suitable outputs.

2x. R-TV (TV and radio FM receiver). 1x. DATA (cable modem).



Mount:	Surface-mounted
Sockets type:	• 1 pcs DATA, • 2 pcs RTV
TV frequency range:	87 ... 1000 MHz
Radio frequency range:	87 ... 1000 MHz
Frequency range for DATA line:	5 ... 65 MHz
TV tap attenuation:	87 ... 862 MHz @ 7.5 max. 8.5 dB 862 ... 1000 MHz @ 8.5 max. 9.5 dB
Radio tap attenuation:	87 ... 862 MHz @ 7.5 max. 8.5 dB 862 ... 1000 MHz @ 8.5 max. 9.5 dB
DATA tap attenuation:	5 ... 65 MHz @ 9.5 max. 10.5 dB
Main features:	• Full, double galvanic isolation between input and outputs • High voltage input protection 2.12 kV / DC • Protection system against core inverse magnetization due to high level signals • Solid, die-cast metal housing
Weight:	0.12 kg
Dimensions:	98 x 80 x 27 mm
Manufacturer / Brand:	TELMOR
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60