

Code: TRN-1/400A

VIDEO BALUN **TRN-1/400A**

The TRN-1/400A is designed to video signals transmission and power supplying via twisted-pair cable (UTP, FTP). Video signal from camera is connect to the TRN-1/400A transmitter input, and transmitted via twisted-pair cable to the TRO-4G/400 or the TRO-1/400 receiver. Both transmitter and receiver units adapt 75Ω coaxial cable impedance to twisted-pair cable impedance, what guarantees the video signal transmission up to 400m.

The TRO-1/400 receiver supplies un-stabilized voltage (maximal up to 45V DC) to twisted-pair cable, and the TRN-1/400A transmitter converts it into 4V ... 14V DC stabilized voltage, what enables power the cameras with thermostat.

The device allows to change the output voltage in range of 4V ... 14V with a potentiometer.

ATTENTION! The TRN-1/400A device is not an autonomous one and operates with TRO-1/400, TRO-4G/400 devices only.



Standard:	<ul style="list-style-type: none"> • AHD - 5 Mpx, • HD-CVI - 8 Mpx 4K UHD, • HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC
Input voltage:	max. 45 V DC
Device type:	Active / Transmitter
Number of channels:	1 Video 1 DC
Coaxial socket voltage range 75Ω (CVBS):	1 Vpp
Output voltage adjustment:	4 V ... 14 V DC
Video transmission range:	<ul style="list-style-type: none"> • 250 m @ 720p - UTP cat. 5e • 150 m @ 1080p - UTP cat. 5e • 400 m @ CVBS - PAL / NTSC - UTP cat. 5e
Output voltage:	12 V DC / max. 900 mA (factory setting)
Attenuation:	<ul style="list-style-type: none"> • 4.43 MHz @ 0.73 dB • 11 MHz @ 1.24 dB • 21 MHz @ 2.16 dB • 38 MHz @ 3.35 dB • 42 MHz @ 3.54 dB • 67.5 MHz @ 3.72 dB
Symmetrical socket impedance:	100 Ω
Connectors type:	BNC Socket Video Cable terminals DC
Symmetrical socket type:	RJ-45 (8-pin, 4 pairs) Socket



DATA SHEET

Power supply distance:	<ul style="list-style-type: none">• Power supply 24 V DC 1080 m @ 250 mA 260 m @ 750 mA• Power supply 29 V DC 1600 m @ 250 mA 500 m @ 750 mA
Weight:	0.09 kg
Dimensions:	118 x 61 x 30 mm
Guarantee:	3 years
Manufacturer / Brand:	DELTA