

Code: FLEX-401

NVR **FLEX-401** 4 CHANNELS +HDMI

The FLEX-401 digital recorder is a professional device applicable in surveillance systems. The H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



Standard:	TCP/IP
Supported resolutions:	4 @ 1920 x 1080 px, 4 @ 1280 x 720 px
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	4 Channels
Audio inputs:	Audio from cameras
Audio outputs:	—
Image compression method:	H.264
Maximal total frame rate:	100 fps @ 1920 x 1080 px, 100 fps @ 1280 x 720 px
Supported hard drives:	1 x 4 TB SATA
Operation modes:	Firmware V4.0[20140322] : • 4 x Main stream (1920 x 1080) + 4 x Sub stream (960 x 576) + 1 Channel played simultaneously • 4 x Main stream (1280 x 720) + 4 x Sub stream (960 x 576) + 4 Channels played simultaneously
Recording modes:	Manual, Motion Detection, Schedule
Bitrate:	40 Mbps
Network protocols:	ONVIF, I8, I9, RTSP ONVIF compliance
External storage devices backup:	Records backup at .mp4 / .avi format to USB (pendrive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Network functions:	Live image view, Playback the records, Backup the records



DATA SHEET

Mobile phones support:	Available applications for mobile systems: iPhone, Android, Windows Mobile, Blackberry, Symbian Meye application - mobile port 5053
Operation temp:	-10 °C ... 55 °C
Alarm inputs / outputs:	—
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	22 x 18 motion zones
Mouse support:	✓
Power supply:	12 V DC / 2 A
Weight:	0.82 kg
Dimensions:	219 x 215 x 50 mm
Supported languages:	English, Polish
Country of origin:	China
Guarantee:	2 years