

Code: JA-180B

## WIRELESS GLASS BREAK DETECTOR **JA-180B** JABLOTRON

Sensor signals an alarm on registering a low-frequency tone (impact sound), followed by a high-frequency tone (sound of broken glass). The sensor starts to analyze a high-frequency channel after receiving the low-frequency sound wave, caused by the impact.

The device is powered by battery, for communication is used the JABLOTRON radio protocol.

**Attention!** Battery not included.



Support:	JABLOTRON 100
Detection:	Glass break detector
Frequency band:	868.1 MHz
Radio communication range (at open area):	max. 100 m
Alarm signaling:	Signal to control panel
Tamper contact:	✓
Battery:	LS(T)14500 (AA 3.6 V 2000 mAh) (not included)
Backup time:	max. 3 years
Protection class (Grade):	Grade 2
Environmental class EN 50130-5:	—
Main features:	<ul style="list-style-type: none"> <li>• The LED to indicate violations in test mode, easy start-up and later maintenance of the system</li> <li>• detection of breaking plate, laminated or tempered glass</li> </ul>
Operation temp:	-10 °C ... 40 °C
Permissible relative humidity:	93 ± 3 %
Color:	White
Weight:	0.060 kg
Dimensions:	107 x 28 x 22 mm
Manufacturer / Brand:	JABLOTRON
Guarantee:	2 years