# DATA SHEET

Code: DRP-024V048W-1AZ

## SWITCHING ADAPTER **DRP-024V048W-1AZ**

Switching adapter installed on the TS35/7.5 or 15 DIN rail, resistant to high operation temperatures (up to 70°C).



| | |
|---|---|
| Adapter type: | Switching |
| Power voltage: | 86 ... 264 V AC |
| Output voltage: | 24 V DC |
| Output voltage adjustment: | 22 ... 26 V |
| Voltage tolerance: | ± 1 % |
| Maximal load: | 2 A |
| Output power: | 48 W |
| Number of outputs: | 1 pcs |
| Efficiency: | 87 % |
| Housing type: | DIN |
| MTBF (Mean Time Between Faults): | 500000 hours |
| Vibration resistance: | IEC60068-2-6, 10 ... 150 Hz max. 5 G for 90 minutes |
| Protections: | • Short-circuit<br>• Overvoltage<br>• Overload protection |
| Operation temp. / Relative humidity: | -20 °C ... 75 °C / < 95 % |
| Weight: | 0.21 kg |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|---|---|
| Dimensions: | 32  x 101  x 100 mm |
| Guarantee: | **5 years** |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60