
# DATA SHEET

Code: OR-DC-619

## CARBON MONOXIDE (CO) DETECTOR **OR-DC-619**

The OR-DC-619 microprocessor-based digital gas detectors are characterized by reliability and low current consumption. A digital temperature compensation feature allows to operate within a wide temperature range.
Gas concentration above the threshold level triggers visual and audible alarm signals. Device should be mounted at a height of about 1.5 m above the floor.




| | |
|---|---|
| Detection: | Carbon Monoxide (CO) |
| Alarm signaling: | • Alarm siren<br>• Blinking LED |
| Gas concentration to trigger alarm: | • 50 ppm for 60 ... 90 minutes<br>• 100 ppm for 10 ... 40 minutes<br>• 300 ppm for max. 3 mins |
| Battery power supply: | 3 x  battery LR6 (AA) (included) |
| Main features: | • Low battery level alarm<br>• Alarm siren 85 dB/m<br>• Test mode<br>• The memory of the last highest concentration of CO, which triggered the alarm<br>• EN 50291-1:2010/A1:2012 compliance<br>• Detector lifetime : 7 years |
| Operation temp: | 0 °C ... 40 °C |
| Weight: | 0.19 kg |
| Dimensions: | 123  x 77  x 35 mm |
| Manufacturer / Brand: | ORNO |
| Guarantee: | 2 years |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60