

Code: BCS-NVR64082M

NVR **BCS-NVR64082M** 64 CHANNELS +eSATA



Standard:	TCP/IP
Supported resolutions:	64 @ 1920 x 1080 px, 64 @ 1280 x 960 px, 64 @ 1280 x 720 px, 64 @ 704 x 576 px
Audio support:	Audio from cameras
Video outputs:	1 pcs HDMI 1 pcs VGA 1 pcs BNC
Audio inputs:	1 pcs Microphone, BNC
Audio outputs:	1 pcs BNC
Image compression method:	H.264 / MPEG-4
Maximal total frame rate:	1600 fps @ 1920 x 1080 px, 1600 fps @ 1280 x 960 px, 1600 fps @ 1280 x 720 px, 1600 fps @ 704 x 576 px
Supported hard drives:	8 x 4 TB SATA + 4 x 2 TB eSATA - HDD Array
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, Alarm Server, IP Search ONVIF
External storage devices backup:	Backup to USB drive (pendrive, external drive), eSATA
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function
Bitrate:	max. 192 Mbps
Network functions:	Full support via network, Remote records copying, Web Server built-in max. 120 on-line users
ONVIF:	2.0

Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS • Windows Phone: Free application wDMSS Lite There are also paid versions of mobile applications: gDMSS Plus, iDMSS Plus, wDMSS plus
Alarm inputs / outputs:	16 pcs / 5 pcs - Relay output
PTZ control:	RS-485 - BCS (PTZ IP) cameras only
Motion Detection:	22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	✓
Power supply:	230 V AC
Weight:	6.86 kg
Dimensions:	440 x 465 x 95 mm
Supported languages:	Polish, English
Country of origin:	China
Manufacturer / Brand:	BCS
Guarantee:	2 years