

## DATA SHEET

Code: MS-35RS

## MONITOR VIDEO, AUDIO, RS-485 MS-35RS 3.5 "

Service color monitor is very helpful for CCTV system configuration. Due to small sizes it can be very quickly and easily connected to the camera or DVR for configuration their parameters.

The device is powered from battery or power supply adaptor. So, it is the perfect test tool for CCTV systems, as well as for other devices with Composite Video (AV) output. An additional advantage is the possibility to power the connected devices with DC 12V and max. 500mA current consumption, and also the long operation time. Monitor is equipped with plastic housing.



Screen size:	3.5 "
Native resolution:	320 x 240 px
Contrast:	400 : 1
Brightness:	250 cd/m <sup>2</sup>
Response time:	10 ms
Image adjustment:	brightness, contrast and color saturation
Video signal standard:	NTSC/PAL auto
Video input:	1 pcs CINCH / USB cable included in the kit
Video output:	1
PTZ control:	RS-485, PELCO-D/P, 1200, 2400, 4800, 9600 b/s - Remote control
Power output:	12 V / 800 mA
Sleep function:	after 2 mins video signal off
Audio input:	1 pcs CINCH / USB cable included in the kit
Audio output:	_
Speaker built-in:	with Mute function





## DATA SHEET

Operation temp:	5 °C 60 °C
Battery power supply:	Batteries: 2200 mAh (included) V DC (power adapter included)
Weight:	0.160 kg
Dimensions:	93 x 74 x 41 mm
Guarantee:	2 years