

Code: ATLO-KRM-102

CODE LOCK **ATLO-KRM-102**

Indoor, autonomous code lock with RFID reader.
Autonomous operation of the device allows the user to:

- Open by using a card or PIN code.
- Remember stored cards or PIN codes.
- Signaling left the door open.
- Acoustic and optical signaling.

Administrator capabilities are following:

- Programming by using the keypad.
- Adding a new card by using the keypad.
- Adding a new card and entering a PIN code.
- Changing the PIN code of the user.
- Deleting the PIN code of the user.
- Setting the lock release time.
- Restoring the default settings.



Cards support:	Unique EM 125kHz
Reading distance of prox-keys:	3 ... 6 cm
Autonomous operation:	✓
Keyboard built-in:	✓
Communication:	Wiegand 26
Doorbell button:	—
Tamper output:	—
Power supply:	12 V DC ± 10%
Maximal current consumption:	25 mA (Standby mode) 60 mA (operation)
Relay contacts load:	1 A / 12 V

Main features:	<ul style="list-style-type: none"> • Number of relay outputs : 1, • 2000 indexed users, • Identification: Card and/or PIN • Blue backlight of the keys • Support for door contact and exit button • Electric strikes and electromagnetic locks support • Reversing bolt support • Tamper protection (detection of removing from mounting surface and enclosure opening) • Alarm output • NO/NC output • Possible connection of the external ATLO-R series reader (read in/out access control)
Operation temp:	-45 °C ... 60 °C
Permissible relative humidity:	10 ... 90 % (non-condensing)
"Index of Protection":	IP40
Housing:	Plastic (ABS)
Color:	Black
Weight:	0.09 kg
Dimensions:	82 x 92 x 21 mm
Manufacturer / Brand:	ATLO
Guarantee:	3 years

