

Code: VMT-071

MONITOR 2xVIDEO **VMT-071** 7 " VILUX

CCTV monitor in plastic housing.

The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination.

The device is designed to continuous work in closed spaces.



| | |
|----------------------------|--|
| Screen size: | 7 " |
| Native resolution: | 800 x 480 px |
| Aspect ratios: | 16 : 10 |
| Matrix type: | TFT-LCD color matrix |
| Matrix backlight: | In LED technology |
| Supported standards: | PAL/NTSC |
| Contrast: | 500 : 1 |
| Brightness: | 250 cd/m ² |
| Viewable angles: | 140 ° horizontal 120 ° vertical |
| Response time: | 25 ms |
| Speakers built-in: | — |
| Signal connectors: | Composite Video (BNC) sockets: 2x in |
| Housing type: | Plastic |
| Monitor mounting standard: | Monitor bracket with adjusted tilt in range 90 ° |
| Power supply: | 12 V DC / 1 A (power adapter included) |

| | |
|-----------------------|--|
| Power consumption: | max. 10 W (operation) < 1 W (Standby mode) |
| Monitor control: | OSD - by monitor control keys |
| Main features: | • Auto Picture Adjustment |
| Operation temp: | -10 °C ... 50 °C |
| Weight: | 0.48 kg |
| Dimensions: | 178 x 119 x 95 mm (with stand) 178 x 119 x 25 mm (without stand) |
| Supported languages: | English, Chinese Simplified, French, Spanish, German, Polish, Portuguese, Russian, Italian |
| Manufacturer / Brand: | VILUX |
| Guarantee: | 2 years |