

Code: POE-8/R19

PATCH PANEL **POE-8/R19**

The POE-8/R19 panel is a passive device used to supply power via UTP cables to terminal devices equipped with PoE ports. To data transmission in twisted-pair cable are normally use wires 1, 2, 3 and 6. The PoE panel injects supply voltage to the 4, 5(+); 7, 8(-) pins/wires.

On the panel front there two rows of RJ-45 ports. Panel can supply power to 8 PoE devices.

The POE-8/R19 is a passive device.

The device features overload protection (polyswitch on each output: the power is switched off by the long flow of high current) and short-circuit protection. The front panel green light LED indicates normal operation of the device.



| | |
|--------------------------------------|--|
| Output voltage: | max. 60 V |
| Number of inputs: | 8 pcs (RJ-45) |
| Number of outputs: | 8 pcs (RJ-45) |
| Maximal output current: | 550 mA / Output |
| Main features: | Pin numbers for RJ-45 connector • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA |
| Protections: | • Short-circuit • Overload |
| LED indicators: | Power supply |
| Housing: | 1 U Rack 19" |
| Operation temp. / Relative humidity: | -10 °C ... 55 °C / < 95 % |
| Weight: | 0.29 kg |
| Dimensions: | 483 x 44 x 36 mm |
| Manufacturer / Brand: | DELTA |
| Guarantee: | 3 years |