

Code: VMT-326M

MONITOR VGA, 2XVIDEO IN, 2XVIDEO OUT, S-VIDEO, HDMI, AUDIO, REMOTE CONTROLLER **VMT-326M** 32 " VILUX

CCTV monitor with solid metal housing. The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination.

It has two types of mounting. as desktop with attached stands and VESA 200.

Monitor is designed to the display of advertising spots from computer in public places such as waiting rooms, etc. Very interesting solution is placing the speakers of the back side of housing. It does not bother listening to the AUDIO from the recorder at the same time does not reduce the area of the monitor front panel.

The device is designed to continuous work in closed spaces.



Screen size:	32 "
Native resolution:	1920 x 1080 px
Aspect ratios:	16 : 9
Matrix type:	TFT-LCD color matrix
Matrix backlight:	In LED technology
Supported standards:	PAL/NTSC
Contrast:	10000 : 1
Brightness:	250 cd/m ²
Viewable angles:	170 ° horizontal 170 ° vertical
Response time:	5 ms
Speakers built-in:	2 x 2.5 W
Signal connectors:	• Composite Video (BNC) sockets: 2x in, 2x out • 1x VGA • 1x HDMI • 1x S-VIDEO • Audio input: (Jack - works with VGA input) • 2x audio input: 2x Cinch L/R - works with BNC input

Housing type:	Metal
Monitor mounting standard:	VESA 200
Power supply:	230 V AC
Power consumption:	< 60 W (operation)
MTBF (Mean Time Between Faults):	50000 h
Monitor control:	OSD - by IR remote controller or monitor control keys
Main features:	• 3D Comb Filter • 3D Noise Reduction • Auto Picture Adjustment
Operation temp:	-20 °C ... 60 °C
Weight:	10.7 kg
Dimensions:	• 744 x 437 x 54 mm (without stand) • 744 x 490 x 202 mm (with stand)
Supported languages:	English, Chinese, French, Spanish, German, Polish, Portuguese, Russian, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years