

Code: POE-802.3AT/24

STABILIZER 48V/12V **POE-802.3AT/24**



The POE-802.3AT/24 allows to supply the devices with DC 12V.
 Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.
 Please pay attention for proper cooling conditions of the power adaptor during work!

| | |
|-----------------------------|--|
| Standards: | PoE (802.3af), PoE (802.3at) |
| Input socket: | RJ-45 |
| Number of inputs: | 1 x RJ-45 socket - PoE |
| Number of outputs: | 1 x RJ-45 plug - on the cable 1 x 2.1/5.5 mm plug on the cable |
| Input voltage: | 44 - 57 V PoE |
| Output voltage: | 12 V DC +/- 10% |
| Output current: | <ul style="list-style-type: none"> • 1.6 A (continuous operation) • 2 A (instantaneous operation) |
| Supported data rates: | <ul style="list-style-type: none"> • Ethernet - 10 Mbps Half Duplex • Fast Ethernet - 100 Mbps Full Duplex |
| Maximal transmission range: | 100 m (DATA) |
| LEDs application: | Power supply PoE - Yellow |
| Certificates: | CE |
| Weight: | 0.068 kg |
| Dimensions: | 94 x 35 x 27 mm |
| Guarantee: | 2 years |

