

Code: VD-M70

VIDEO DOORPHONE KIT **VD-M70**



DOOR STATION:	
Sensor:	1/3 " CMOS
Camera view angle:	~ 92 °
IR illuminator:	Built-in Infra-Red illuminator enables night monitoring
proximity reader built-in:	—
Video output:	1 Vpp / 75 Ω
Power supply:	15 V DC
Power consumption:	< 2 W
Maximal voltage and operating current of the electric strike/lock:	24 V / 6 A DC - OD ("open drain") type
Housing:	Metal, Waterproof
Color:	Dark graphite
Operation temp:	-20 °C ... 60 °C
Weight:	0.192 kg
Dimensions:	51 x 125 x 44 mm
INDOOR PANEL:	
Shield:	7 " - TFT LCD
Resolution:	800 x 480

Main features:	• Plug & Play • Number of ring-tones : 24 • Ultra-flat hands-free monitor, with speakerphone • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume • 4-wire cable installation max. 200 m • Door lock (strike) - 2-wire cable installation • Can be extended with additional monitor and camera • Communication : via cable (duplex) • cable included : 4.7 m
Power supply:	15 V DC / 1200 mA (power adapter included)
Power consumption:	< 1.1 W Standby ≤ 6 W Operation
Color:	Graphite
Operation temp:	-10 °C ... 50 °C
Weight:	0.510 kg
Dimensions:	255 x 165 x 32 mm
Guarantee:	2 years