

Code: SMS-5/12

## MULTISWITCH **SMS-5/12** 5 INPUTS / 12 OUTPUTS SIGNAL



Inputs:	4 x 950 MHz ... 2150 MHz , 1 x 47 MHz ... 790 MHz
Outputs:	12 x 47 ... 2150 MHz
TV amplification (cable pre-correction):	2 dB
SAT amplification (cable pre-correction):	2 dB
Isolation:	<ul style="list-style-type: none"> <li>• Interpolarized H/V : 28 dB</li> <li>• Between inputs TV/SAT : 28 dB</li> <li>• Between inputs SAT/SAT : 30 dB</li> <li>• Outputs : 30 dB</li> </ul>
Return loss:	TV input : 10 dB SAT input : 11 dB Outputs : 10 dB
Maximal output level SAT:	101 dB $\mu$ V (EN50083-3)
Maximal output level TV:	85 dB $\mu$ V (EN50083-5)
Switching signals:	13 V / 18 V 0, 22 kHz
LNB power supply:	max. 600 mA
Pre-amplifiers powering:	12 V DC
Power supply:	90 ... 240 V AC/50Hz
Weight:	1.024 kg
Dimensions:	465 x 120 x 70 mm
Manufacturer / Brand:	SIGNAL
Guarantee:	2 years