

Code: DCTXP-2

WIRELESS MAGNETIC CONTACT **DCTXP-2** PARADOX

The DCTXP-2 wireless detector (magnetic contact) is used to protection the windows and doors. Additionally the device is equipped with input, which enables connecting any wire detector.



Support:	PARADOX: SPECTRA SP (RTX-3, RX-1, K-32_LX), MAGELLAN MG, Digiplex EVO (RTX-3, K-641_LX)
Detection:	<ul style="list-style-type: none"> • Opening the door or window, • The input, which enables connecting any wire detector
Break distance:	~ 10 mm
Alarm signaling:	Signal to control panel
Frequency range:	433 MHz - PARADOX MAGELLAN
Radio communication range (at open area):	max. 60 m
Alarm inputs:	NO/NC
Battery:	2 x AAA 1.5 V (not included)
Backup time:	~ 3 years
Current consumption:	max. 5 mA
Main features:	<ul style="list-style-type: none"> • Input response time : 45 ms • Tamper protections • The ability to connect 1 alarm zone

Complies with norms:	EN 61000-6-3, EN 50130-4 EN 60950-1 ETSI EN 300 220-2, ETSI EN 301 489-1, ETSI EN 301 489-3 EN 50581
Operation temp:	-10 °C ... 55 °C
Color:	White
Weight:	0.05 kg
Dimensions:	<ul style="list-style-type: none">• Transmitter : 32 x 112 x 25 mm• Magnet A : 14 x 44 x 16.5 mm
Country of origin:	Canada
Manufacturer / Brand:	PARADOX
Guarantee:	2 years