DATA SHEET

Code: GT-CI11V1-28W

IP CAMERA **GT-CI11V1-28W** - 720p 2.8 mm GEMINI TECHNOLOGY

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 720p. Very easy operation by Internet Explorer browser allows the users to convenient and remote support, and also remote management of the camera. Included camera software enables management and integrated monitoring of many network cameras. Its using allows to create large surveillance system.
ICR - The movable IR filter allows to perfect colors reproduction in daylight and wide gray-scale with high sharpness of the image at night mode.



Standard:	TCP/IP
Sensor:	1/4 " OmniVision OV9712 CMOS
Digital Image Processor:	Hisilicon 3518E
Scanning system:	Progressive
Matrix size:	1.37 Mpx
Resolution:	1280 x 720 - 720p 720 x 576 - D1
Lens:	2.8 mm
View angle:	65 ° (manufacturer data)
Range of IR illumination:	15 m
S/N ratio:	> 50 dB
Memory card slot:	–
Image compression method:	H.264, MJPEG
Alarm inputs / outputs:	–
Audio:	–

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Bitrate:	16 ... 8000 kbps
Main stream frame rate:	max. 25 fps - 720p
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SNMP, ONVIF
WEB Server:	Built-in
Max. number of on-line users:	10 10
Main features:	• Possibility to change the resolution, quality and bit rate • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Motion Detection • Privacy zones - max. 4 • Mirror - Mirror image • Time mark and image description • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Day/Night mode - configurable • Possibility to add different privileges to the users
Mobile phones support:	Port 5053 • Android: Free application MEye • iOS (iPhone): Free application Meye • Windows Phone: Free application Meye
Default IP address:	192.168.1.188
Default admin user / password:	admin / (null)
Web browser access ports:	80, 554, 1935 - Firmware V1.0, V1.1 80, 5050, 5051, 5052 - Firmware V4.0 - V4.3
PC client access ports:	5050, 5051, 5052
Mobile client access ports:	5053
Port ONVIF:	80 - Firmware V1.0, V1.1 8000 - Firmware V4.0 - V4.3
RTSP URL:	rtsp://ip_address:554/ch01.264 - Main stream rtsp://ip_address:554/ch01_sub.264 - Sub stream
Color:	White
Vandal-proof:	–
Power supply:	12 V DC / 260 mA
Housing:	Dome - Plastic
"Index of Protection":	IP40
Operation temp:	-20 °C ... 55 °C
Dimensions:	Ø 92 x 75 mm
Weight:	0.188 kg
Supported languages:	English, Polish
Manufacturer / Brand:	GEMINI TECHNOLOGY

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Guarantee:	2 years

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60