

Code: TL-WR802N

ROUTER **TL-WR802N** 2.4 GHz 300 Mbps TP-LINK

The TL-WR802N mini-size router is ideal for home and travel use. Simple and easy installation and operation.

Due to 5 operation modes, the TL-WR802N is an extremely versatile device.

The TL-WR802N ensures advanced access control and QoS, its DHCP server supports static assignment of IP addresses.



Frequency range:	2.4 GHz ... 2.4835 GHz
Antenna type:	Internal antenna
Standards:	IEEE 802.11 b/g/n
Baud rates:	300 Mbps
Modulation type:	OFDM, BPSK, QPSK
LAN ports:	1 x 10/100 Mbps (RJ-45)
LED indicators:	Power, Connection status
Receiver sensitivity:	<ul style="list-style-type: none"> • 270M: -65dBm@10% PER • 130M: -70dBm@10% PER • 108M: -82dBm@10% PER • 54M: -73dBm@10% PER • 11M: -82dBm@8% PER • 6M: -86dBm@10% PER • 1M: -90dBm@8% PER
DDNS:	<ul style="list-style-type: none"> • No-IP • DynDNS • Comexe
DHCP server:	✓
Firmware update:	✓





DATA SHEET

Operation modes:	<ul style="list-style-type: none">• Router,• AP,• Client,• Repeater,• Bridge
Protections:	64/128/152-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK Table of access / access-deny according to MAC addresses of client cards Internet access filtering via filters of IP addresses, MAC addresses and ports of TCP/IP protocol
Management interface:	Web browser
Transmitter power:	< 20 dBm
Power supply:	<ul style="list-style-type: none">• 5 V DC / 600 mA (power adapter included)• from USB port
Main features:	<ul style="list-style-type: none">• MAC address cloning• Firewall• Internet access filtering• Static / dynamic routing
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	90 % (non-condensing)
Weight:	0.170 kg
Dimensions:	57 x 57 x 18 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years