

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity; 2. Improper results of operation of the product or products related with it;

3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.

The MXVR6212 is a mobile recorder designed to use in coaches, city buses, busses, trams, subway, corporate and personal vehicles and special vehicles ie. lorries, police cars, prison or military cars, ambulances. The device has been specially designed so that exhibited increased resistance to oscillations and vibrations.

The power cables of the MXVR6212 are connected to the car's battery and ignition (analogous to radio receiver), so when you turn the ignition device automatically begins recording the audio-video data.





DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

MXVR6212



User Manual Code: MXVR6212 AHD, HD-TVI, HD-CVI, PAL MOBILE DVR **MXVR6212** 8 CHANNELS + 4 IP CHANNELS DAHUA

Video inputs:8 pcs M12, 4 pin socket + 4 pcs RJ-45 · IP camerasVideo outputs:1 pcs VGA 1 pcs M12, 4 pin socketAudio inputs:8 pcs - Audio from camerasAudio outputs:1 pcs M12, 4 pin socketResolution of recording video files:1 pcs XI2 & pin socketSupported hard drives:2 pcs 2.5 " SATAImage compression method:Smart H.264 / H.264GPS:-G-Sensor:-Rs 465:2 pcsRs 465:2 pcsRs 476:-Rs 476:2 pcsRs 476:2 pcsRs 476:2 pcsRs 476:-Rs 476:2 pcsRs 476:2 pcsRs 476:2 pcsRs 476:2 pcsRs 476:-Rs 476:-	Standard:	AHD, HD-TVI, HD-CVI, CVBS (switchable)
Video outputs:I jes M12, 4 µin socketAudio inputs:B pcs - Audio from camerasAudio outputs:I pcs M12, 4 µin socketResolution of recording video files:1920 x 1080 @ 25 fpsSupported hard drives:2 pcs 2.5 " SATAImage compression method:Smart H.264 / H.264GPS:-G-Sensor:-Rs-485;2 pcsRs-485;2 pcsRs-232;-Port USB:1 x USB 3.0, 1Autin inputs / outputs:9 / 2SIM socket:-Amin features:-Audio recording after power on '-Alarms and maintenance events registration '-Alarms and maintenance events registration '-Alarms and meintenance events registration '-Alarms and errors memory reading '-Backup to USB memuPower supply:6 V36 V DCPower consumption:312 WOperation temp:30 °C60 °CWeight:206 kgDimensions:190 x 180 x 50 mmManifacturer / Brand:190 x 180 x 50 mm	Video inputs:	8 pcs M12, 4-pin socket + 4 pcs RJ-45 - IP cameras
Audio outputs:1 pcs M12, 4 pin socketResolution of recording video files:1920 x 1080 @ 25 fpsSupported hard drives:2 pcs 2.5 * SATAInage compression method:Smart H.264 / H.264GPS:-G-Sensor:-RS-485:2 pcsRS-485:2 pcsRS-232:✓Port USB:1 x USB 3.0 , 1 x USB 2.0 *Alarm inputs / outputs:9 / 2SIM socket:-For use:-Main features:* Powering the cameras with 12V DC voltage directly from recorder * Adtor powering Adtor Detection Detection Adtor Detection Detection Adtor Detection Detection Adtor Detection Detection * Adtor recording after power on * Adtor recording after	Video outputs:	
Resolution of recording video files:1920 x 1080 @ 25 fpsSupported hard drives:2 pcs 2.5 * SATAImage compression method:Smart H.264 / H.264GPS:-G-Sensor:-RS-485:2 pcsRS-232:-Port USB:2 x USB 3.0, 1 1 x USB 2.0Alarm inputs / outputs:9 / 2SIM socket:-Main features:-Main features:Short outputs:Power supply:6 V36 V DCPower supply:6 V36 V DCPower supply:30 °C60 °CPowers:30 °C60 °CWeight:20 mmDimensions:190 x 180 x 50 mmMain featurer:190 x 180 x 50 mm	Audio inputs:	8 pcs - Audio from cameras
Supported hard drives:2 pcs 2.5 " SATAImage compression method:Smart H.264 / H.264GPS:-G-Sensor:-RS-485:2 pcsRS-232:-Port USB:2 x USB 3.0, 1 1 x USB 2.0Alarm inputs / outputs:9 / 2SIM socket:-Main features:-Main features:•Power supply:6 V36 V DCPower supply:6 V60 °COperation temp:30 °C 60 °CWeight:2.06 kgDimensions:140 X 50 mmMain features:9.07 X 50 mmOperation temp:0 AtlUA	Audio outputs:	1 pcs M12, 4-pin socket
Image compression method:Smart H.264 / H.264GPS:-G-Sensor:-R5-485:2 pcsR5-232:-Port USB:2 x USB 3.0 , 1 x USB 2.0Alarm inputs / outputs:9 / 2SIM socket:-Table Series (Series Constraint)-Main features:-Main features:-Pover consumption:6 V 36 V DCPower consumption:512 WOperation temp:-30 °C 60 °CWeight:2.06 kgDimensions:100 x 180 x 50 mmMana featurer / Brand:004 LAUMater Mana Method Series Constraint)Mater Method:-State Method:-Mater Method:-	Resolution of recording video files:	1920 x 1080 @ 25 fps
GPS: - G-Sensor: - RS-485: 2 pcs RS-232: - Port USB: 2 x USB 3.0, 1 Alarm inputs / outputs: 9 / 2 SIM socket: - Alarm sinputs / outputs: 9 / 2 SIM socket: - Alarm sinputs / outputs: 9 / 2 Sim socket: - Main features: -Novering the cameras with 12V DC voltage directly from recorder 'Motion Detection 'Motion Detection 'Alarms and maintenance events registration 'Alarms and errors memory reading 'Backup to USB drive (pendrive, external drive) 'Mouse support 'Nouse support 'Dish, English menu Power consumption: <12 W	Supported hard drives:	2 pcs 2.5 " SATA
G-Sensor:-RS-485:2 pcsRS-232:-Port USB:2 x USB 3.0 , 1 x USB 2.0Alarm inputs / outputs:9 / 2SIM socket:-Ford USB::Nain features::Power supply:6 V36 V DCPower consumption::Operation temp::30 °C 60 °CVieight::00 x 180 x 50 mmDimensions:idott a vieight and in tempMain feature / Brand::00 x 180 x 50 mm	Image compression method:	Smart H.264 / H.264
RS-485: 2 pcs RS-232: ✓ Port USB: 2 x USB 3.0, 1 x USB 2.0 Alarm inputs / outputs: 9 / 2 SIM socket: – Main features: · Powering the cameras with 12V DC voltage directly from recorder · Autron Detection · Auto recording after power on · Alarms and maintenance events registration · Alarms and maintenance events registration · Alarms and errors memory reading · Backup to USB drive (pendrive, external drive) · Mouse support · Alarms and errors memory reading · Backup to USB drive (pendrive, external drive) · Mouse support · Remote control · Polish, English menu Power supply: 6 V 36 V DC Power consumption: ≤ 12 W Operation temp: .30 °C 60 °C Weight: 2.06 kg Dimensions: 190 x 180 x 50 mm Amuacturer / Brand: HAUA	GPS:	-
RS-232: ✓ Port USB: 2 x USB 3.0 , 1 x USB 2.0 Alarm inputs / outputs: 9 / 2 SIM socket: — Main features: • Powering the cameras with 12V DC voltage directly from recorder • Alarms and maintenance events registration • Recording of the traveled route of the vehicle using the GPS receiver • Alarms and errors memory reading • Backup to USB drive (pendrive, external drive) • Moises support • Remote control • Polish, English menu Power supply: 6 V 36 V DC Power consumption: ≤ 12 W Operation temp: -30 °C 60 °C Weight: 2.06 kg Dimensions: 190 x 180 x 50 mm Mandacturer / Brand: DAHUA	G-Sensor:	-
Port USB: 2 x USB 3.0, 1 x USB 2.0 Alarm inputs / outputs: 9 / 2 SIM socket: - Main features: • Powering the cameras with 12V DC voltage directly from recorder • Motion Detection • Adarms and maintenance events registration • Recording after power on • Alarms and mointenance events registration • Recording of the traveled route of the vehicle using the GPS receiver • Motion Detection • Alarms and rorrs memory reading • Backup to USB drive (pendrive, external drive) • Mouse support • Mouse support • Polish, English menu Power consumption: ≤ 12 W Operation temp: -30 °C 60 °C Weight: 2.06 kg Dimensions: 190 x 180 x 50 mm Manufacturer / Brand: DAHUA	RS-485:	2 pcs
PORT USB: 1 x USB 2.0 Alarm inputs / outputs: 9 / 2 SIM socket: - Main features: • Powering the cameras with 12V DC voltage directly from recorder • Motion Detection • Auto recording after power on • Auto recording of the traveled route of the vehicle using the GPS receiver • Alarms and maintenance events registration • Recording of the traveled route of the vehicle using the GPS receiver • Alarms and errors memory reading • Backup to USB drive (pendrive, external drive) • Polish, English menu Power supply: 6 V 36 V DC Power consumption: ≤ 12 W Operation temp: 60 °C Weight: 2.06 kg Dimensions: 190 x 180 x 50 mm Manufacturer / Brand: DAHUA	RS-232:	*
SIM socket: - Main features: • Powering the cameras with 12V DC voltage directly from recorder Main features: • Powering the cameras with 12V DC voltage directly from recorder Main features: • Powering the cameras with 12V DC voltage directly from recorder Nain features: • Powering the cameras with 12V DC voltage directly from recorder Nain features: • Powering the cameras with 12V DC voltage directly from recorder • Autor scording after power on • Alarms and maintenance events registration • Recording of the traveled route of the vehicle using the GPS receiver • Alarms and errors memory reading • Backup to USB drive (pendrive, external drive) • Mouse support • Mouse support • Remote control • Polish, English menu • Polish, English menu Power consumption: ≤ 12 W Operation temp: • 30 °C 60 °C Weight: 2.06 kg Dimensions: 190 x 180 x 50 mm Manufacturer / Brand: DAHUA	Port USB:	
Main features:Powering the cameras with 12V DC voltage directly from recorder • Motion Detection • Autor recording after power on • Alarms and maintenance events registration • Recording of the traveled route of the vehicle using the GPS receiver • Alarms and errors memory reading • Backup to USB drive (pendrive, external drive) • Mouse support • Remote control • Polish, English menuPower supply:6 V 36 V DCPower consumption:≤ 12 WOperation temp:-30 °C 60 °CWeight:2.06 kgDimensions:190 x 180 x 50 mmManufacturer / Brand:DAHUA	Alarm inputs / outputs:	9 / 2
Main features:• Motion Detection • Auto recording after power on • Alarms and maintenance events registration • Recording of the traveled route of the vehicle using the GPS receiver • Alarms and errors memory reading • Backup to USB drive (pendrive, external drive) • Mouse support • Mouse support • Polish, English menuPower supply:6 V 36 V DCPower consumption:≤ 12 WOperation temp:-30 °C 60 °CWeight:2.06 kgDimensions:190 x 180 x 50 mmManufacturer / Brand:DAHUA	SIM socket:	-
Power consumption: ≤ 12 W Operation temp: -30 °C 60 °C Weight: 2.06 kg Dimensions: 190 x 180 x 50 mm Manufacturer / Brand: DAHUA	Main features:	 Motion Detection Auto recording after power on Alarms and maintenance events registration Recording of the traveled route of the vehicle using the GPS receiver Alarms and errors memory reading Backup to USB drive (pendrive, external drive) Mouse support Remote control
Operation temp: -30 °C 60 °C Weight: 2.06 kg Dimensions: 190 x 180 x 50 mm Manufacturer / Brand: DAHUA	Power supply:	6 V 36 V DC
Weight: 2.06 kg Dimensions: 190 x 180 x 50 mm Manufacturer / Brand: DAHUA	Power consumption:	≤ 12 W
Dimensions: 190 x 180 x 50 mm Manufacturer / Brand: DAHUA	Operation temp:	-30 °C 60 °C
Manufacturer / Brand: DAHUA	Weight:	2.06 kg
	Dimensions:	190 x 180 x 50 mm
Guarantee: 2 years	Manufacturer / Brand:	DAHUA
	Guarantee:	2 years

Front view:







Front panels of the sockets:



The device is equipped with a mobile rack for 2 SATA 2.5" hard drives:





DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

2024-04-27

MXVR6212









Rear view:





DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

2024-04-27

MXVR6212





In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg

