

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order.

If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
2. Improper results of operation of the product or products related with it;
3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.

The TPC-BF5401-TB7 Thermal Imaging Camera is a modern solution that allows to detect the presence of people, animals and vehicles regardless of prevailing vision conditions. The device is equipped with sensitive VOx microbolometer that allows to observe the objects in fog, smoke and in the absence of illumination. An additional advantage of the TPC series cameras is the ability to detect fire and send a signal to the alarm control panel when it occurs.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.





User Manual

Code: TPC-BF5401-TB7

IP THERMAL IMAGING CAMERA **TPC-BF5401-TB7** - 1.4 Mpx, 7.5 mm DAHUA

Standard:	TCP/IP, CVBS
Sensor:	Uncooled VOx microbolometer
Matrix size:	400 x 300 px
Pixel pitch:	17 μ m
Thermal sensitivity (NETD):	≤ 40 mK @ F1.0
Spectral range:	8 μ m ... 14 μ m
Resolution:	1280 x 1024 - 1.4 Mpx , 1280 x 960 - 960p , 1280 x 720 - 720p , 400 x 300
Lens:	7.5 mm
View angle:	54 °
Video output:	CVBS, PAL - 1 Vpp / 75 Ω , BNC
RS-485 interface:	✓
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method:	H.265 / H.264M / H.264H / H.264B / MJPEG
Alarm inputs / outputs:	2 / 2
Audio:	<ul style="list-style-type: none">• Audio input• Audio output
Temperature measurement:	<ul style="list-style-type: none">• Spot• Line• Area max. 12 positions
Temperature measurement range:	<ul style="list-style-type: none">• -20 °C ... 150 °C,• 0 °C ... +550 °C
Main stream frame rate:	25 fps @ 1280 x 1024
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	HTTP, HTTPS, TCP/IP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE IPv4/IPv6, SNMP, QoS, UPnP, NTP
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	✓
Mobile phones support:	Port 3777 <ul style="list-style-type: none">• Android: Free application DMSS• iOS (iPhone): Free application DMSS
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777



User Manual

Code: TPC-BF5401-TB7

IP THERMAL IMAGING CAMERA **TPC-BF5401-TB7** - 1.4 Mpx, 7.5 mm DAHUA

Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features:	<ul style="list-style-type: none">• DDE (Digital Detail Enhancement) - for high dynamic images, it automatically adjusts the contrast of the image to the temperature parameters. The DDE function is the ideal tool for quick and accurate testing of electrical installations. Thanks to it the image is much more detailed and sharpened• 2D-DNR, 3D-DNR - Digital Noise Reduction• ROI - improve the quality of selected parts of image• AGC - Automatic Gain Control• EIS - Electronic Image Stabilization• Mirror - Mirror image• D-ZOOM - Digital Zoom : 19 x• IVS analysis : crossing the line (tripwire), intrusion, object detection (people, vehicle), fire detection
Power supply:	<ul style="list-style-type: none">• 12 V DC / 1.2 A,• PoE (802.3af),• ePoE
Power consumption:	max. 13 W
Housing:	Compact - Metal
Color:	White
Operation temp:	-40 °C ... 70 °C
"Index of Protection":	IP67
Weight:	1.4 kg
Dimensions:	291 x 104 x 97 mm
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------