

User Manual

Code: K2-PLASTIPOX/25G PROFFESSIONAL 2-COMPONENT ADHESIVE **K2-PLASTIPOX/25G** TUBE 25 g K2

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

- 1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
- 2. Improper results of operation of the product or products related with it;
- 3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

Epoxy adhesive for professional bonding of all kinds of surfaces, especially plastic ones. Permanently bonds most combinations of dissimilar materials such as plastics, metals, ceramics, porcelain, fiberglass, glass, PVC, leather, wood and many other materials.

The adhesive has high resistance to impact, water, gasoline, kerosene and oils. Perfectly fills gaps.

The K2-PLASTIPOX/25G is offered in the form of adhesive in a syringe. The innovative syringe applicator guarantees simple use and optimal dosing of both components at the same time. The closed syringe protects the product from drying out, thanks to which the adhesive retains its properties long after opening and does not dry out.

 $\begin{tabular}{ll} \textbf{Attention!} & The adhesive does not bond with polyethylene (PE) and polypropylene (PP) plastics. \end{tabular}$



Package:	Tube 25 g
----------	-----------



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



User Manual

${\bf Code:~K2\text{-}PLASTIPOX/25G}\\ {\bf PROFFESSIONAL~2\text{-}COMPONENT~ADHESIVE~K2\text{-}PLASTIPOX/25G~TUBE~25~g~K2}\\$

Color:	White
Main features:	Type of glue - epoxy adhesive Application: Plastic, PVC, ABS, Metal, Stainless steel, Glass, Ceramics, Porcelain, Fiberglass, Natural Leather, Wood, and others, Bond strength: 305 kg/cm², Glue bonding time: 7 minutes - initial, 2 h - Bond strength 75 %, 24 h - Full hardening Ability to move the glued object after 15 minutes The adhesive has high resistance to impact, water, gasoline, kerosene and oils. Maximum thickness of the gaps to be filled: 10 mm Temperature strength of fully cured adhesive bond: -55 °C 120 °C
Dimensions:	182 x 40 x 37 mm
Manufacturer / Brand:	K2



Package:



User Manual



PACKAGE

Dimensions (L x W x H): 0x0x0 mm

Gross Weight: 0 kg