



User Manual

Code: C52IG-5HAXD2HAXD-TC

ACCESS POINT C52IG-5HAXD2HAXD-TC hAP ax², Wi-Fi 6, 2.4 GHz, 5 GHz, 574 Mbps + 1200 Mbps
MIKROTIK

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order.

If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
2. Improper results of operation of the product or products related with it;
3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.

The C52IG-5HAXD2HAXD-TC access point broadcasts 2 separate wireless networks in the 5 GHz band with speed 1200 Mb/s and in the 2.4 GHz band with speed 574 Mb/s. Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band - all at the same time.

The device can be powered using the included power adapter or via Passive PoE (18 ... 28 V DC) via the PoE IN port.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes. The set includes a practical stand that allows the device to be placed vertically, horizontally or wall mounted.

Supports 802.11ax standard - the next generation of Wi-Fi.



Frequency range:	2.4 GHz, 5 GHz ,
Antenna type:	2x2 MIMO - built-in • 4.5 dBi @ 2.4 GHz • 4 dBi @ 5 GHz
Standards:	IEEE 802.11 b/g/n/ax @ 2.4 GHz , IEEE 802.11 a/n/ac/ax @ 5 GHz , Wave2 support
Baud rates:	574 Mbps + 1200 Mbps
LAN ports:	4 x 10 / 100 / 1000 Mbps LAN 1 x 10 / 100 / 1000 Mbps Uplink
LED indicators:	Power, User, 4 x Ethernet, WAN, PoE OUT




User Manual

Code: C52IG-5HAXD2HAXD-TC

ACCESS POINT **C52IG-5HAXD2HAXD-TC** hAP ax², Wi-Fi 6, 2.4 GHz, 5 GHz, 574 Mbps + 1200 Mbps
MIKROTIK

Receiver sensitivity:	2.4 GHz : <ul style="list-style-type: none">• 1M : -100 dBm• 11M : -94 dBm• 6M : -96 dBm• 54M : -80 dBm• MCS0 : -96 dBm• MCS7 : -75 dBm• MCS9 : -70 dBm• MCS11 : -67 dBm 5 GHz : <ul style="list-style-type: none">• 6M : -96 dBm• 54M : -80 dBm• MCS0 : -96 dBm• MCS7 : -75 dBm• MCS9 : -70 dBm• MCS11 : -67 dBm
DHCP server:	✓
Firmware update:	✓
Protections:	WPA3, Firewall
Operating system:	MikroTik RouterOS
Management interface:	Web browser
Default IP address:	192.168.88.1
Transmitter power:	max. 24 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz
Power supply:	• 12 ... 28 V DC - 24 V DC / 1.2 A (power adapter included) • 18 ... 28 V DC - Passive PoE
Power consumption:	max. 27 W
Main features:	<ul style="list-style-type: none">• Built-in 5-port switch• Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments• 2x2 MIMO / Dual-chain @ 2.4 GHz, 5 GHz• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network• Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source• IPsec• Passive PoE - 1 x Input / Output (port Internet/PoE IN/OUT)• Possible power supply via Passive PoE via eth1/Poe OUT port - 0.6 A, 16.8 W (max)• Mode button• RESET button
Operation temp:	-40 °C ... 50 °C
Weight:	0.27 kg
Dimensions:	120 x 100 x 33 mm
Manufacturer / Brand:	MikroTik
Guarantee:	2 years

Front panel:



Rear view:



Rear panel:



Mode button:



In the kit:



PACKAGE



User Manual

Code: C52IG-5HAXD2HAXD-TC

ACCESS POINT **C52IG-5HAXD2HAXD-TC** hAP ax², Wi-Fi 6, 2.4 GHz, 5 GHz, 574 Mbps + 1200 Mbps
MIKROTIK

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------