



User Manual

Code: DS-2CD2T87G2P-LSU/SL(4MM)(C)/BLACK

IP CAMERA **DS-2CD2T87G2P-LSU/SL(4MM)(C)/BLACK** PANORAMIC ColorVu - 7.4 Mpx 2 x 4 mm
Hikvision

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
2. Improper results of operation of the product or products related with it;
3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.

The IP camera is equipped with 2 high quality image sensors and 2 lenses with 4 mm focal length. Thanks to its unique design, the camera has a 180° viewing angle.

Attention! The camera of the ColorVu series does not have a black and white mode. Thanks to fit the camera in a very sensitive sensor and the LED illuminator emitting visible light in white, the device allows to obtain a clear, colorful image in all lighting conditions. PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	TCP/IP
Sensor:	2 x 1/1.8 " Progressive Scan CMOS
Matrix size:	2 x 3.7 Mpx - 8 Mpx (total)
Scanning system:	Progressive
Resolution:	5120 x 1440 - 7.4 Mpx
Lens:	2 x 4 mm
View angle:	180 ° (horizontal) 44 ° (vertical)
White light LED illuminator range:	40 m
RS-485 interface:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	1 / 1
Audio:	<ul style="list-style-type: none"> • Microphone built-in • External microphone input • Audio output • Bi-directional audio streaming support • Digital Noise Reduction
Main stream frame rate:	20 fps @ 7.4 Mpx
Network interface:	10/100 Base-T (RJ-45)
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect



User Manual

Code: DS-2CD2T87G2P-LSU/SL(4MM)(C)/BLACK

IP CAMERA **DS-2CD2T87G2P-LSU/SL(4MM)(C)/BLACK** PANORAMIC ColorVu - 7.4 Mpx 2 x 4 mm
Hikvision

Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.64
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	<ul style="list-style-type: none">• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
WEB Server:	Built-in
Max. number of on-line users:	6
ONVIF:	✓
Main features:	<ul style="list-style-type: none">• WDR - 130 dB - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• ROI - improve the quality of selected parts of image• NAS - Network Attached Storage support• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect• Active deterrence function - Light and sound alarm• White light (LED) illuminator built-in : 4 LEDs• BLC - Back Light Compensation• HLC - High Light Compensation (spot)• AGC - Automatic Gain Control• Possibility to change the resolution, quality and bit rate• Configurable: brightness, contrast, saturation• Smart motion detection (with recognizing people and vehicles)• Intelligent image analysis - crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, scene changing
Power supply:	<ul style="list-style-type: none">• 12 V DC / 790 mA,• PoE (802.3af)
Power consumption:	<ul style="list-style-type: none">• ≤ 9.5 W @ 12 V DC• ≤ 10.5 W @ PoE
Housing:	Compact, Metal
Color:	Black
Vandal-proof:	—
"Index of Protection":	IP67
Operation temp:	-30 °C ... 60 °C
Weight:	1.45 kg
Dimensions:	119 x 105 x 305 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
SAP Code:	311323807



User Manual

Code: DS-2CD2T87G2P-LSU/SL(4MM)(C)/BLACK

IP CAMERA **DS-2CD2T87G2P-LSU/SL(4MM)(C)/BLACK** PANORAMIC ColorVu - 7.4 Mpx 2 x 4 mm
Hikvision

Manufacturer / Brand:	Hikvision
Guarantee:	3 years

Front view:



Side view:




Bottom view:



Memory card slot and "Reset" button:



Mounting side view:



Connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------