

Code: BCS-L-DIP12FSR3-AI1 IP VANDALPROOF CAMERA BCS-L-DIP12FSR3-AI1 - 1080p 2.8 mm BCS Line

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

- 1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
- 2. Improper results of operation of the product or products related with it;
- 3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.



Code: BCS-L-DIP12FSR3-AI1 IP VANDALPROOF CAMERA BCS-L-DIP12FSR3-AI1 - 1080p 2.8 mm BCS Line

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

 \mbox{PoE} powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	TCP/IP
Sensor:	1/2.8 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p, 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens:	2.8 mm
View angle:	• 106 ° (manufacturer data) • 100 ° (our tests result)
Range of IR illumination:	30 m
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	-
Audio:	Microphone built-in Audio detection
Main stream frame rate:	25 fps @ 1080p
Network interface:	10/100 Base-T (RJ-45)
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	✓



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Code: BCS-L-DIP12FSR3-AI1 IP VANDALPROOF CAMERA BCS-L-DIP12FSR3-AI1 - 1080p 2.8 mm BCS Line

Mobile phones support: - Android iOS (iP) Default IP address: Default admin user / password: Web browser access ports: PC client access ports: Mobile client access ports: 7777 Mobile client access ports: 80, 3777 Port ONVIF: 80 rtsp://adm Main strentsp://adm Stream WDR - 3D-DNI ROI - in BLC - E HLC - II	inistrator password should be set at the first start 77 min:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 -
Default admin user / password: Web browser access ports: PC client access ports: Mobile client access ports: Port ONVIF: RTSP URL: RTSP URL: **Tsp://adm. Main stre. rtsp://adm. stream **WDR - 3D-DNI - ROI - in BLC - E - HLC - II -	min:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - eam min:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub 120 dB - Wide Dynamic Range R - Digital Noise Reduction mprove the quality of selected parts of image Back Light Compensation High Light Compensation (spot) Movable InfraRed filter
Default admin user / password: Web browser access ports: PC client access ports: Mobile client access ports: Port ONVIF: RTSP URL: RTSP URL: **Tsp://adm Main strentsp://admin.strentsp://	min:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - eam min:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub 120 dB - Wide Dynamic Range R - Digital Noise Reduction mprove the quality of selected parts of image Back Light Compensation High Light Compensation (spot) Movable InfraRed filter
PC client access ports: Mobile client access ports: 237777 Port ONVIF: RTSP URL: RTSP URL: **Tsp://adm Main strentsp://adm stream** **WDR - **3D-DNI** **ROI - in **BLC - E** **HLC - F** **TSP URL: **Tsp://adm Stream** **WDR - ** **BLC - E** **HLC - F** **HLC - F** **HLC - F** **HLC - F** **TSP URL: **Tsp://adm Stream** **WDR - ** **HLC - F** **H	min:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - eam min:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub 120 dB - Wide Dynamic Range R - Digital Noise Reduction mprove the quality of selected parts of image Back Light Compensation High Light Compensation (spot) Movable InfraRed filter
Mobile client access ports: Port ONVIF: 80 rtsp://adn Main stre rtsp://ads stream • WDR - • 3D-DNI • ROI - ir • BLC - E • HLC - I	eam min:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub 120 dB - Wide Dynamic Range R - Digital Noise Reduction mprove the quality of selected parts of image Back Light Compensation High Light Compensation (spot) Movable InfraRed filter
Port ONVIF: RTSP URL: rtsp://adn Main stre rtsp://ads stream • WDR - • 3D-DNI • ROI - in • BLC - E • HLC - I	eam min:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub 120 dB - Wide Dynamic Range R - Digital Noise Reduction mprove the quality of selected parts of image Back Light Compensation High Light Compensation (spot) Movable InfraRed filter
RTSP URL: rtsp://adm Main stre rtsp://adm stream • WDR - • 3D-DNI • ROI - ir • BLC - E • HLC - F	eam min:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub 120 dB - Wide Dynamic Range R - Digital Noise Reduction mprove the quality of selected parts of image Back Light Compensation High Light Compensation (spot) Movable InfraRed filter
RTSP URL: Main stre rtsp://adi stream • WDR - • 3D-DNI • ROI - ir • BLC - E • HLC - F	eam min:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub 120 dB - Wide Dynamic Range R - Digital Noise Reduction mprove the quality of selected parts of image Back Light Compensation High Light Compensation (spot) Movable InfraRed filter
• 3D-DNI • ROI - ir • BLC - E • HLC - I	R - Digital Noise Reduction mprove the quality of selected parts of image Back Light Compensation High Light Compensation (spot) Movable InfraRed filter
Main features: Day/Ni Auto W AGC - A Mirror Motion Privacy SMD P Intellig	Thite Balance Automatic Gain Control - Mirror image Detection - max. 4 zones y zones - max. 4 PLUS - searching for an object classified as: human, motor vehicle yent Image Analysis: crossing the line (tripwire), intrusion - classification of nd vehicles
Power supply: • PoE (80 • 12 V Do	02.3af), C / 390 mA
Power consumption: $0.56 \text{ V} \le 5.6 \text{ V} \le 4.7 \text{ V}$	N @ PoE N @ 12 V DC
Housing: Dome - M	Metal
Color: White	
"Index of Protection": IP67	
Vandal-proof: IK10	
Operation temp: -40 °C	. 60 °C
Weight: 0.35 kg	
Dimensions: Ø 110 x	81 mm
Supported languages: Polish, E.	inglish
Manufacturer / Brand: BCS Line	e
Guarantee: 3 years	

Internal view of the housing:





Code: BCS-L-DIP12FSR3-AI1
IP VANDALPROOF CAMERA BCS-L-DIP12FSR3-AI1 - 1080p 2.8 mm BCS Line



Memory card slot:



Mounting side view:



Code: BCS-L-DIP12FSR3-AI1
IP VANDALPROOF CAMERA BCS-L-DIP12FSR3-AI1 - 1080p 2.8 mm BCS Line



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm

Gross Weight: 0 kg